

Waterproof distribution box												
Ways (HA)	8	12	8	12	12	18	12	18	18	26	22	22
Ways (EKDB10)	6	9	9	13	13	18	13	15	18	26	22	22
IP degree	IP65											
Input or output connector	PG or MC4(installation optional)											
DC MCB												
Rated current	32A		32A/63A		32A		63A/125A		32A/63A		50/100A	
Poles	2	4	2	4	2	4	2	4	2	4	2	4
Rated breaking capacity	6kA/10kA											
Surge protective device												
Experimental Level	II		II		II		II		II		II	
Max. operation voltage	600V	1000V	600V	1000V	600V	1000V	600V	1000V	600V	1000V	600V	1000V
In (8/20 μ s)	20kA		20kA		20kA		20kA		20kA		20kA	
I _{max} (8/20 μ s)	40kA		40kA		40kA		40kA		40kA		40kA	
Voltage protection level	2.6kV	4kV	2.6kV	4kV	2.6kV	4kV	2.6kV	4kV	2.6kV	4kV	2.6kV	4kV
Poles	2 pole/3 pole		2 pole/3 pole		2 pole/3 pole		2 pole/3 pole		2 pole/3 pole		2 pole/3 pole	
DC Fuse												
Rated operation voltage	1000V		1000V		1000V		1000V		1000V		1000V	
Rated current	15A (8~32A)		15A (8~32A)		15A (8~32A)		15A (8~32A)		15A (8~32A)		15A (8~32A)	
Fuse size	10x38mm		10x38mm		10x38mm		10x38mm		10x38mm		10x38mm	
Environment												
Operating Temperature	-25℃ to +55℃											
Humidity	0.95											
Altitude	2000m											
Installation	Wall Mounting											